

# Certificate of Conformity

This is to Certify **DriStud Cool Window Flashing Tape**

## Product Description

DriStud Cool Window Flashing Tape is a self-adhesive, pressure sensitive, polyethylene membrane material tape with a release backing. The tape is branded with the DriStud Cool Window Flashing Tape branding and the CodeMark logo.

## Complies with the Building Code of New Zealand:

When specified and installed in accordance with the requirements of this certificate, DriStud Cool Window Flashing Tape will comply with the following provisions of the NZ Building Code;

B1 Structure – B1.3.1, B1.3.2, B1.3.3 (a), (c), B1.3.4 (a), (b), (c), (d)

B2 Durability – B2.3.1 (b), B2.3.2 (a)

E2 External Moisture – E2.3.2 (contributes to), E2.3.7 (a), (b), (c)

F2 Hazardous Building Material – F2.3.1

## Subject to the following conditions and limitations:

1. Must be installed in accordance with the DriStud Cool Window Flashing Tape Installation Guides, Rev-02 November 2018, these are available at [www.dristud.co.nz](http://www.dristud.co.nz)
2. The scope of this certificate covers the use of DriStud Cool Window Flashing Tape in buildings;
  - Up to 10m in height, and
  - With a risk score less than 20, when evaluated against the E2/AS1 risk matrix, and
  - In wind zones up to extra high as defined in NZS3604:2011.
3. Installation at an ambient and substrate temperature of less than -6°C falls outside the scope of this certificate.
4. The scope of the certificate covers the use of DriStud Cool Window Flashing Tape with DriStud Wall Wrap and rigid air barriers made from plywood, OSB or fibre cement.



**CODEMARK**<sup>TM</sup>  
®

## Product Use and Scope

DriStud Cool Window Flashing Tape is intended for use in new and existing buildings in conjunction with an underlay or rigid air barrier. It is used around framed joinery openings and penetrations, providing a secondary weather resistant barrier. It is designed to be used in conjunction with air seals and joinery flashing systems, but not as a substitute.

DriStud Cool Window Flashing Tape may also be used at joinery heads to seal flashing upstands to the building wrap. Where a rigid underlay has been installed, DriStud Cool Window Flashing Tape may be used to seal all junctions and penetrations.

It is suitable for use with timber and steel framed buildings as well as masonry structures. It may be used where the environment temperature fluctuates between -28°C to 80°C.

## Certificate Holder

TCL Hunt Ltd  
7 Fisher Cres, Mt Wellington,  
Auckland, 1644  
Web: [www.dristud.co.nz](http://www.dristud.co.nz)  
Ph: 09 526 2700



**JAS-ANZ**



[www.jas-anz.org/register](http://www.jas-anz.org/register)

**CodeMark Certification Body**

AsureQuality, 11 Hull Road  
Mt Maunganui  
New Zealand  
Tel. 0508 00 11 22  
[www.asurequality.com](http://www.asurequality.com)

John McKay, Chief Executive Officer, AsureQuality Limited

**Date of Issue**

15<sup>th</sup> July 2015

**Certificate Number**

**AQ-160715-CMNZ**  
(Rev 1 – November 2018)

TCL Hunt Limited will notify AsureQuality Ltd in accordance with Regulation 15 of the Building (Product Certification Regulations 2008)

"This certificate is issued by an independent certification body accredited by the product certification accreditation body appointed by the Chief Executive of the Ministry of Business, Innovation and Employment (MBIE) under the Building Act 2004.

The MBIE does not in any way warrant, guarantee, or represent that the building method or product the subject of this certificate conforms with the New Zealand Building Code, nor accept any liability arising out of the use of the building method or product.

The MBIE disclaims, to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages, and costs arising as a result of the use of the building method(s) or product(s) referred to in this certificate.

This certificate may only be reproduced in its entirety."